

Gear motor product range

| Model | Mounting flange | Displacement range cm ³ /rev [in ³ /rev] | Max rated pressure bar [psi] | Features |
|--------------|---|---|---------------------------------|---|
| SKU1 SKM1 | European 4-bolt and SAE A-A 2-bolt | 0.26 - 12 [0.2 - 0.7] | 250 [3625] | Unidirectional (SKU1) and bi-rotational (SKM1) - SAE A-A 9T splined, 1:8 & 1:5 taper, 12 and keyed 12.7 mm - O-ring boss ports, Euro 4-bolt ports - European/metric options |
| SNU2 SNM2 | European 4-bolt and SAE A 2-bolt flanges | 8.4 - 25.2 [0.5 - 1.5] | 250 [3625] | Unidirectional (SNU2) and bi-rotational (SNM2) - SAE A 9T spline, 1:8 and 1:5 taper, 15 and 15.875 mm keyed - O-ring boss ports, European 4-bolt ports - Integral valves (special rear cover) - Fan drive versions with integral control and relief valves - Radial case drain option - European/metric options |
| SNU3 SNM3 | European 4-bolt flange SAE B 2-bolt | 22.1 - 63.4 [1.4 - 3.9] | 250 [3625] | Unidirectional (SNU3) and bi-rotational (SNM3) - SAE B 13T spline, 1:8 and 1:5 taper, 22; 22.225 and 24mm keyed - O-ring boss ports, SAE B and Euro 4-bolt ports, split flange ports - Motor mounted fan drive versions control and relief valves - European/metric options |
| MYCP | SAE A 2-bolt flange | 9.5 - 31.8 [0.6 - 1.9] | 240 [3481] | Unidirectional and bi-rotational - SAE A 11T spline and 9T spline - 0.75in. straight. key shaft - O-ring boss ports - A/C checks available |