



## Recovery Winches

Verricelli Winch	Strato di fune Cable Layer	Tiro diretto Line Pull [daN]	Q.tà fune tamburo Cable Capacity [m]	Velocità fune Cable Speed [m/min]	Diametro fune consigliato Recommended Cable Dia. [mm]	Rapporto di riduzione Gear Reduction Ratio
<b>T27 IN</b>	1°	2700	6.8	12	10.0	1 : 5.77
	2°	2300	15	14		
	3°	2000	24	16		
	4°	1725	35	19		
<b>T36 IN</b>	1°	3600	5.7	10	12	1 : 5.77
	2°	2950	12.5	12		
	3°	2500	21	14		
	4°	2150	30.5	16		
<b>T46 IN</b>	1°	4600	5.7	8.5	12	1 : 5.40
	2°	3750	12.5	10		
	3°	3200	21	12		
	4°	2750	30.5	14		
<b>T60</b>	1°	6000	7.5	6.5	14	1 : 14.8
	2°	4850	16.5	8		
	3°	4070	27	9.5		
	4°	3500	40	11		
<b>T100</b>	1°	10000	8	8	16	1 : 23
	2°	8200	18	10		
	3°	6950	30	12		
	4°	6000	43	14		
<b>T200</b>	1°	20000	9.5	5	22	1 : 64.5
	2°	16350	21	6		
	3°	13850	35	7.3		
	4°	12000	51	8.5		
<b>T300</b>	1°	30000	12.5	4.5	26	1 : 60.5
	2°	24650	27.5	5.5		
	3°	20950	45	6.5		
	4°	18200	65.5	7.5		