

PRESSURE RELIEF VALVES



DIRECT, PILOT AND SOLENOID OPERATED RELIEF VALVES

MODEL	MAXIMUM PRESSURE	SIZE	MAXIMUM FLOW	TYPE OF VALVE
	bar (psi)		lpm (gpm)	
RV-01	315 (4500)	1/8"	2 (0.53)	DIRECT OPERATED
RV-02		1/4"	16 (4.23)	DIRECT OPERATED
DB-03G	350 (5076)	3/8"	250 (66.05)	PILOT OPERATED
DB-06G		3/4"	500 (132.09)	PILOT OPERATED
DB-10G		1/1/4"	650 (171.72)	PILOT OPERATED
DBW-03G	350 (5076)	3/8"	250 (66.05)	SOLENOID OPERATED
DBW-06G		3/4"	500 (132.09)	SOLENOID OPERATED
DBW-10G		1/1/4"	650 (171.72)	SOLENOID OPERATED
RV-03	315 (4500)	3/8"	90 (23.78)	PILOT OPERATED
RV-06		3/4"	200 (52.84)	PILOT OPERATED
RV-10		1/1/4"	400 (105.68)	PILOT OPERATED
SRV-03	315 (4500)	3/8"	90 (23.78)	SOLENOID OPERATED
SRV-06		3/4"	200 (52.84)	SOLENOID OPERATED
SRV-10		1/1/4"	400 (105.68)	SOLENOID OPERATED

COIL TYPES AVAILABLE : A1 : AC110 60HZ, A115 : AC115 50HZ, A230 : AC230 50HZ, A2 : AC220 60HZ
D1 : DC12, D2 : DC24, R1 : RF110 60HZ/50HZ, R2 : RF220 60HZ/50HZ