



MODEL	MAXIMUM PRESSURE	SIZE	MAXIMUM FLOW	WORKING VOLTS
	bar		lpm	
FW-01G	250	1/8"	14	12 -24 DC, 110-220 AC
FW-02G	315	1/4 "	80	12 -24 DC, 110-220 AC
FW-03G	315	3/8 "	120	12 -24 DC, 110-220 AC
FWH-04G	250	1/2"	200	12 -24 DC, 110-220 AC
FWH-06G	350	3/4 "	500	12 -24 DC, 110-220 AC
FWH-10G	250	1-1/4"	1100	12 -24 DC, 110-220 AC
GDFW/GD SERIES	315	1/4 "-1-1/4"	80-650	FLAME PROOF
WPFW SERIES	315	1/4"-1-1/4"	80-1100	WATER PROOF

3C2		2B2B		2B2BL	
3C3		2B3B		2B3BL	
3C4		2B4B		2B4BL	
3C5		2B5B		2B5BL	
3C6		2B6B		2B6BL	
3C7		2B7B		2B7BL	
3C9		2B9B		2B9BL	
3C10		2B10B		2B10BL	
3C11		2B11B		2B11BL	
3C12		2B12B		2B12BL	
3C25		2B25B		2B25BL	
3C29		2B29B		2B29BL	

2B2	
2B3	
2B8	
2B2L	
2B3L	
2B8L	

Mechanical Position

2D2	
2D3	
2D8	

No return spring and no mechanical positioning

2N2	
2N3	
2N8	